



DATWYLER UPS

UNINTERRUPTIBLE
POWER
SUPPLY

**SUSTAINABLE POWER PROTECTION
FOR YOUR IT INFRASTRUCTURE**

2022



DATWYLER

DATWYLER UPS

An Uninterruptible Power Supply is crucial in today's digital era most especially the businesses' operational activities are heavily dependent on electronic systems and IT infrastructure. UPS plays a significant role in ensuring that the organization's overall activities run seamlessly, and without interruption.

The Datwyler Uninterruptible Power Supply (DUPS) series provides small to medium power transformerless UPS.

It offers guaranteed power protection for connected electronics. When power is interrupted or fluctuates outside the safe levels, the Datwyler UPS instantly provides a clean battery backup power and surge protection for connected and sensitive devices. It is also designed to a high standard that can be customized based on the customer's technical and budget requirements.



KEY FEATURES

- Higher efficiency
- Fully digital control
- Intelligent monitoring
- Flexible battery configuration
- Safety and reliable protection
- Intelligent charging method

TYPICAL INDUSTRY APPLICATIONS



Data Centres



Office Buildings



Government Buildings



Shopping Malls



Education



Transport Hubs

A rapidly maturing market:

- . Data Centre
- . Office buildings
- . Government Buildings
- . Retails
- . Education
- . Logistics
- . Healthcare and many others

DATWYLER UPS

10~50 KVA (3 PHASE)

TOWER / RACK MOUNTED

TECHNICAL FEATURES

- Online double conversion
- Power factor (PF=1.0)
- Cold start
- Full digital control (DSP)
- Intelligent Monitoring Function
- Support Economic (ECO) operation mode
- Parallel redundancy function
- Three level inverter topology
- Estimated remaining time displayed on the LCD
- Power saving
- Safe and reliable protection
- Flexible battery configuration
- Load Bus Synchronization (LBS) function
- Intelligent Charging Method
- Strong load capacity
- Flexible Installation
- Communication port: RS-232 / USB (Optional SNMP card)



MODEL	40070000ZY	40070100ZY	40070200ZY	40070300ZY	40070400ZY	40070500ZY	40070600ZY
Capacity (VA/Watts)	10,000	15,000	20,000	25,000	30,000	40,000	50,000
INPUT							
Nominal voltage	380/400/415Vac, (3Ph+N+PE)						
Operating voltage range	138~485Vac						
Frequency range	40Hz-70Hz (auto-detect)						
Power factor	≥0.99						
OUTPUT							
Output voltage	380/400/415Vac, (3Ph+N+PE)						
Power factor	1.0						
Harmonic distortion	≤2% with linear load and ≤4% with non linear load						
Voltage regulation	±1%						
SYSTEM FEATURES							
Transfer time	Utility to Battery : 0ms; Utility to bypass: 0ms						
Protection	short circuit, overload, over temperature, battery low, fan fault alarm						
Overload	Load≤110%: last 60min,≤125%: last 10min,≤150%: last 1min						
Backfeed	Support						
Alarm	overload, utility abnormal, UPS fault, battery low, etc.						
PHYSICAL							
Standard model	Dimensions (Dx WxH)	670×440×130 (3U)				800×440×175 (4U)	
	Net weight	25	27~28		45	48	
ENVIRONMENT							
Humidity	20-90% RH @ 0-40° C (non-condensing)						
Noise level	<55dB		<56dB		<58dB		

DATWYLER UPS

6~10 KVA (1:1 PHASE)

TOWER / RACK MOUNTED

TECHNICAL FEATURES

- Online double conversion
- Power factor (PF=0.9)
- Cold start
- Full digital control (DSP)
- Intelligent Monitoring Function
- Efficiency up to 93.5%
- Support Economic (ECO) operation mode
- Input current harmonic: 3%
- ECO function
- Batteries: 16, 18 or 20 pieces (optimized)
- Wide input voltage range: 120~276 VAC
- Wide input frequency range: 45~55 Hz / 54~66 Hz \pm 0.5 Hz
- Input over / under voltage protection
- Communication port: RS-232 / USB (Optional SNMP card)



MODEL	40014800ZY	40014900ZY
Capacity (VA/Watts)	6k / 5.4k	10k / 9k
INPUT		
Nominal voltage	220 / 230 / 240 VAC (L+N+PE)	
Operating voltage range	120 ~ 276 VAC	
Operating frequency range	45 ~ 55 Hz / 54 ~ 66 Hz \pm 0.5 Hz	
Power factor	\geq 0.99	
OUTPUT		
Output voltage	220 / 230 / 240 VAC	
Power factor	0.9	
Efficiency	> 93.5%	
Frequency	Line mode	\pm 1% / \pm 2% / \pm 4% / \pm 5% / \pm 10% of the rated frequency (optional)
	Battery mode	50 / 60 (\pm 0.1) Hz
Harmonic distortion (THDv)	\leq 2% with linear load \leq 5% with non-linear load	
SYSTEM FEATURES		
Transfer time	Utility to battery : 0 ms / Utility to bypass: 0 ms	
Overload	Line mode	Load \leq 110% : last 60 min; \leq 125% : last 10 min; \leq 150% : last 1 min; >150% turn to bypass mode
	Bypass mode	40 A (input breaker) 63 A (input breaker)
Short circuit	Hold whole system	
Overheat	Line mode: switch to bypass; backup mode: shut down UPS immediately	
Battery low	Alarm and switch off	
Self-diagnostics	Upon power on and software control	
EPO (optional)	Shut down UPS immediately	
Battery	Advanced battery management	
Noise suppression	Complies with EN62040-2	
Audible and visual alarms	Line failure, battery low, overload, system failure	
PHYSICAL		
Dimensions	02 RackU	
Net weight (kg)	23	25
PHYSICAL OF BATTERY BANK		
Dimensions (D x W x H)	720 x 443 x 131 mm (3U)	
Net weight (kg)	56	62



DATWYLER UPS

1~3 KVA (1:1 PHASE)

TOWER / RACK MOUNTED

TECHNICAL FEATURES

- Online double conversion
- Power factor (PF=0.9)
- Cold start
- Full digital control (DSP)
- Intelligent Monitoring Function
- Efficiency up to 90%
- Support Economic (ECO) operation mode
- Input current harmonic: 3%
- Estimated remaining time displayed on the LCD
- Hot swappable battery pack
- Emergency power off system
- Settable frequency converter mode
- Flexible Installation (Tower or rack mounted options)
- Communication port: RS-232 / USB (Optional SNMP card)



MODEL	40014640ZY	40014650ZY	40014700ZY	
Capacity (VA/Watts)	1000 / 900	2000 / 1800	3000 / 2700	
INPUT				
Nominal voltage	200/208/220/230/240 VAC or 100/110/115/120/127 VAC			
Input voltage range	55~150 VAC or 110~300 VAC @ 60% load, 80~145 VAC or 160~300 VAC @ 100% load			
Frequency range	45~55 Hz / 55~65 Hz (auto-detect)			
Power factor	≥0.99 @ nominal voltage (100% load)			
OUTPUT				
Output voltage	200/208/220/230/240 VAC or 100/110/115/120/127 VAC			
Power factor	0.9 pF			
Harmonic distortion	≤3% THD (linear load) ≤6% THD (non-linear load)			
Transfer time	AC to DC	zero		
EFFICIENCY				
AC mode	90%	91%	91%	
Battery mode	85%	88%	86%	
PHYSICAL				
Standard model	Dimensions (D x W x H)	430 x 440 x 86.5 mm	552 x 440 x 86.5 mm	710 x 440 x 86.5 mm
	Net weight	8.9 kg	10.1 kg	12 kg
ENVIRONMENT				
Humidity	20-90% RH @ 0-40° C (non-condensing)			
Noise level	<50dB @ 1 m			
MANAGEMENT				
LCD	Load level, battery level, AC mode, battery mode, bypass mode, fault indicators			
Smart RS-232 / USB (preferential)	External Modbus card supported by RS232, Software supports Windows Family, Linux, FreeBSD			
Optional SNMP	Power management from SNMP manager and web browser			



DATWYLER

SWITZERLAND

Dätwyler IT Infra AG
Gotthardstrasse 31
6460 Altdorf
T +41 41 875-1268
F +41 41 875-1986
info.itinfra.ch@datwyler.com
www.ITinfra.datwyler.com

GERMANY

Dätwyler IT Infra GmbH
Auf der Roos 4-12
65795 Hattersheim
T +49 6190 8880-0
F +49 6190 8880-80
info.itinfra.de@datwyler.com
www.ITinfra.datwyler.com

Dätwyler IT Infra GmbH
Lilienthalstraße 17
85399 Hallbergmoos
T +49 811 998633-0
F +49 811 998633-30
info.itinfra.de@datwyler.com
www.ITinfra.datwyler.com

AUSTRIA

Dätwyler IT Infra GmbH
Niederlassung Österreich
Liebermannstraße A02 403
2345 Brunn am Gebirge
T +43 1 8101641-0
F +43 1 8101641-35
info.itinfra.at@datwyler.com
www.ITinfra.datwyler.com

ITALY

Datwyler IT Infra S.r.l.
Via dei Campi della Rienza, 30
39031 Brunico (BZ)
T +39 031 928277
info.ITinfra.it@datwyler.com
www.itinfra.datwyler.com

CZECH REPUBLIC

Datwyler IT Infra s.r.o.
Ústecká 840/33
405 02 Děčín
T +420 417 580110
F +420 417 580139
info.itinfra.cz@datwyler.com
www.ITinfra.datwyler.com

CHINA

Datwyler (Suzhou) IT Infra Co., Ltd.
No. 218, East Beijing Road
Taicang Economic Development Zone
Jiangsu Province, 215413 / P.R. China
T +86 512 3306-8066
F +86 512 3306-8049
info.itinfra.cn@datwyler.com
www.ITinfra.datwyler.cn

Datwyler (Suzhou) IT Infra Co., Ltd.
Shanghai Branch
Room C308, 3F, Tower C, No. 333,
Shuhong Road Minhang District
Shanghai, 201106 / P. R. China
T +86 21 3253-2885
F +86 21 6813-0298
info.itinfra.cn@datwyler.com

Datwyler (Suzhou) IT Infra Co., Ltd.
Beijing Branch
Room 16B2, West Wing, Han Wei Plaza No. 7,
Guang Hua Rd, Chaoyang District
Beijing, 100020 / P. R. China
T +86 10 5971-4288/7776
F +86 10 5971-4277
sales.office.bj.cn@datwyler.com

Datwyler (Suzhou) IT Infra Co., Ltd.
Guangzhou Branch
A, 7 FL, Gaosheng Building
No. 109, Tiyu Rd. W., Tianhe District
Guangzhou, 510620 / P. R. China
T +86 20 3879-1200
F +86 20 3879-1105
sales.office.gz.cn@datwyler.com

SINGAPORE

Datwyler IT Infra Pte. Ltd.
2 Venture Drive
Vision Exchange #19-15/16/17
608526 Singapore
T +65 68631166
F +65 68978885
info.itinfra.sg@datwyler.com
www.ITinfra.datwyler.com

UNITED ARAB EMIRATES

Datwyler Middle East FZE
Jebel Ali Free Zone
LB 15, Second Floor, Room #10
P.O. Box 263480
Dubai
T +971 4 4228129
F +971 4 4228096
info.itinfra.ae@datwyler.com
www.ITinfra.datwyler.com

Datwyler IT Infra Solutions LLC
Unit 1003 - 1005, 10th Floor, IB Tower
Business Bay
Dubai
T +971 4 4228129
F +971 4 4228096
info.itinfra.ae@datwyler.com
www.ITinfra.datwyler.com